



MI	Code	Ean Code	Pcs
750	1PI750	8020089997864	12
2000	1PI002	8020089997857	6
5000	1PI005	8020089997840	4

**Vantaggi**

- Ravviva il colore
- Antimacchia
- Applicabile su superfici umide
- Non lascia effetti traslucidi
- Non ingiallisce
- Nessun odore sgradevole
- Facile manutenzione

**Advantages**

- Enhances natural colour
- Antistain
- No plastic effects
- Maintains natural effect
- Apply able on damp surfaces
- Low odour
- Easy maintenance



# IDROWET

**“EFFETTO BAGNATO”  
MARMI E PIETRE  
NATURALI  
INTERNO/ESTERNO**



**PAVIMENTI - COLONNE  
TAVOLI - DAVANZALI  
BALAUSTRE - BALCONI**

Tattamento ad effetto bagnato ecologico, specifico per pavimenti levigati o grezzi in marmo, granito e pietre naturale. Altamente consigliabile per marmi anticati e ciottoli, il prodotto conferisce una gradevole tonalità calda alla pietra, esaltandone colori e venature. Di facile applicazione.

**Modo d'uso**



Applicare su superfici perfettamente pulite (utilizzare il prodotto POWERCLEAN con una diluizione a 1:30 per la pulizia preventiva; per la rimozione di cere e trattamenti precedenti usare SOLV o DEWAX; attendere l'asciugatura). Stendere il prodotto in modo uniforme sulla superficie da trattare. Si consiglia di applicare una sola stesura di prodotto, se si volesse effettuare una seconda stesura attendere almeno 12 ore. Attendere almeno 24 ore prima di utilizzare il pavimento. Non applicare sulle superfici lucide.

**Resa**

Il consumo indicativo varia da 15-30 m<sup>2</sup>/litro.

**“WET LOOK”  
EFFECT MARBLE  
AND NATURAL STONE  
INTERNAL/EXTERNAL**



**FLOORS - COLUMNS  
TABLES - WINDOW SILLS  
BALCONIES**

Ecological “wet look” treatment specific for honed and textured marble, granite and natural stone. Highly recommended for antique material such as sandblasted, tumbled or cobblestone surfaces. Product enhances the stones natural texture and colours while supplying a pleasant wet look effect. Easy application.

**How to use**



Apply to perfectly dry clean surfaces (for existing floors, use POWER CLEAN diluted in water using a ratio of 1:30 for surface pre clean; to remove existing coatings, waxes or previous applied treatments use SOLV or DEWAX as directed). Allow the floor to dry completely. Apply the product in a uniform way by brush or cloth. One coat is recommend, however if a second application is required, allow 12 hours between each application. Allow 24 hours for complete drying before using the treated surface. Do not apply on polished surfaces.

**Coverage**

Indicated coverage varies from 15-30 m<sup>2</sup>/litre.

