

UNIVERSAL ANTISTAIN - ANTIHUMIDITY

DESCRIPTION

Anti-stain and anti-humidity treatment based on water, for surfaces such as **Marble– Granite (also glossy) Limestone, Cotto and natural stone.**

CHARACTERISTICS AND PLUS

- **TRANSPIRANT**
- **DOES NOT YELLOW**
- **PROTECTS FROM STAINS** (Coffee, oil, water, etc.)

USE	YIELD	DURATION
MARBLE– GRANITE – NAT. STONES	from 15 to 25 m ² /lt	Treated with 2 hands and maintained : 24 months
LIMESTONE	from 5 to 10 m ² /lt	Treated with 2 hands and maintained : 24 months
COTTO	from 4 to 12 m ² /lt	Treated with 2 hands and maintained : 24 months

NEW SURFACES

Apply the product in uniform way on clean and dry surfaces before grouting. Apply a second hand after 3-4 hours. Leave it dry for 24 hours before grouting. Clean the floor with monobrush or soft felt

EXISTING FLOORS

Apply on dry and clean surfaces. Apply the product in uniform way Leave it dry for few hours and then remove any residue with glass wool.

NOTE: READY TO USE product. Drying time is about 12 hours at 25° C and 24 hours at 15° C. Do not apply at lower temperatures than 10° C and under direct sun. During drying period, protect the surface from water and humidity. Product can be applied with : Roller with short hair– Wax applier – Spray pump.

The information in this technical sheet is based on the specifications and potential use known to us. however, this data does not imply any legal obligation or liability whatsoever

CHEMICAL-PHYSICAL PROPERTIES

Aspect and color	Colorless liquid
Density	1,075 kg/lt
Odor	Typical
Flash point	> 61°C

Stabilimento di produzione
FARMICOL SPA

Corso Europa, 85-91 – 20020 Solaro (MI) Italy
info@farmicol.com - +39 02 84505



Worldwide Distributor
MAF CHEMICAL SA

Corso San Gottardo, 54 – 6830 Chiasso (CH)
export@maf-sa-ch