# 12ME AXOL COOL MTL TECHNICAL DETAILS SHEET (TDS)

Revision del 04-2018

## MULTIMETAL EMULSIFIABLE MINERAL OIL

#### **DESCRIPTION**

Safe and versatile. Excellent for shaving removal working on all kind of material (steels, ferrous materials, copper and its alloys, aluminum and its alloys, cast iron.)

#### **ADVANTAGES**

- High cutting performances and tools long life.
- High stability and corrosion protection.
- Free from secondary ammines, boron, chlorine, and biocides creating formaldehyde.

#### **DILUTIONS**

Steels and cast iron: Dilute from 5% to 7% in water Dilute from 6% to 8% in water **Aluminum:** Copper and its alloys: Dilute from 6% to 10% in water

### **AVAILABLE PACKAGING**

5 liters cod. 04MF05 - 210 liters cod. 04MF21

Odor	Chewingum
Emulsion	Faint and milky
Specific weight	0,950 kg/lt
pH at 5%	9.2
Refractometric factor	1
IP 287 (corrosion test)	Passes at 3%
Mineral oil content	45%

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever

Manufacturing plant FARMICOL SPA Corso Europa, 85-91 – 20020 Solaro (MI) Italy info@farmicol.com - +39 02 84505





